SAFETY AND PRODUCTIVITY SOLUTIONS

GENERAL PURPOSE HANDHELD

HH490 Handheld 2D Area-Imaging Scanner

HH490 is designed for commercial environments requiring high speed 1D/2D scanning operations. The imager is able to read bar codes rapidly and continuously, even when reading damaged, partially obscured, or poorly printed bar codes.

Overview



eedback

The HH490 is a new generation of handheld 2D area-imaging scanner, designed to fulfill a wide variety of customers' scanning needs in various applications and scenarios. Examples include membership identification, payment at shopping malls and supermarkets, hotel registration, applications at hospitals and schools, or any place where data needs to be read and identified quickly. HH490 offers excellent 1D and 2D barcode scanning performance at an affordable price. It provides fast scanning for a variety of scanning needs, helps customers quickly obtain data, simplifies operational procedures, and greatly improves the management efficiency of your business. Put simply, the HH490 makes scanning easier and faster! To handle today's commercial deployment challenges and large-scale infrastructures, the HH490 is equipped with Honeywell's advanced EZ Config and POS drivers, which greatly simplify the configuration process and saves time. HH490 is fully backward-compatible with existing HH400 accessories, it helps original customers greatly reduce cost and protect original investment.

Specifications

FEATURES

Features

• Honeywell Operational Intelligence

DIMENSIONS

Overall Dimensions

• 72.5mm×125mm×154mm (2.85 in *4.92 in *6.06 in)

Decode Capability

• 1D/2D

Depth of Field

• 35mm-430mm(13mil UPC-A)

Motion Tolerance

• 75 cm/s

Scan Pattern

Array

Scanning Range

• 35mm-430mm(13mil UPC-A)

Brightness

• 0 - 100000 lux

HARDWARE

Host System Interface

• USB, RS-232

Wireless

Corded

Engine Type

• 2D

Aimer Type

• Area Image

ELECTRICAL

Smart Battery

• N/A

ENVIRONMENTAL

Storage Temperature Range

Operating Humidity

• -40°C to 60°C (-40°F to 140°F)

• 0% to 95% relative humidity

Protection Ratings

• IP40

STANDARDS & APPROVALS

Tumble Specifications

• 250, 0.5 m (1.6 ft tumbles)

Drop Specifications

• 1.2m

OTHERS

For Use With

• EZ Config Tool

Operating Power

• 2 W

Warranty Duration

• 3 years

Form Factor

• Gun shape

nput Voltage

• 4 - 5.5 V DC

Power Connector Type

• usb

Application

• Point of Sale, Retail

Operating Temperature

• 0 - 50 °C32 - 122 °F

Feedba